

# Wascomat W-Series 100G Coin/Card Washers

## Dial-in to profitability with reliable 100 G-force Wascomat washers with Compass Control.

Wascomat's W-series washers combine world-class reliability with innovative features and programmability. Featuring 100 G-force extraction and Compass Control, Wascomat washers increase your profits, lower utility costs, and eliminate laundry headaches. We make it affordable and easy to upgrade your laundry!



Available in 20, 25, 30, 45, 62 and 77 lb. capacities. Stainless or white front panels.



Compass Control puts you in control of your laundry operations. One knob does it all!

Wascomat's 100 G-force washers with Compass Control continue our tradition of excellence in technology, design, and quality:

- Lowest water consumption in the industry. Control important functions such as exact water levels, wash times and number of rinses—with a simple turn of a dial.
- Single phase simplicity in 120 or 220 volt.
- Inverter driven motor for smooth and quiet operation, and high efficiency.
- Soft-grip, slip-lock door handle for trouble-free operation. Durable in any environment.
- Door unlocks immediately at the end of final cycle. Wascomat washers are the only machines that have instant door open and close. No delays.
- Unique 4-compartment supply dispenser lets the customer (or attendant) conveniently load all laundry supplies before starting the wash.
- Riveted unibody steel construction eliminates welds for strength and durability.
- Outstanding coin vault security.
- Interchangeable parts from one machine size to another.

## Features and benefits:

Wascomat's Compass Control provides the ultimate in flexibility:

- Customize wash programs to lower costs, and meet customer demands.
- Five built-in programs and the capability to easily add or delete programs.
- Create fully customized programs for your specific market using Wash Program Manager.
- Heavy Soil and Extra Rinse options increase store revenue and customer satisfaction.
- Display wash program information in two languages simultaneously.
- Value pricing. Set different prices for different wash programs and option keys.
- Use optional X-10 promotion-pricing system to set discounts for different days and hours each week on specific machines.

## Environmentally responsible.

Wascomat equipment is accredited according to the ISO14001 Environmental Management System and ISO9001 Quality Management System. With more than a century of experience behind every machine, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

**Most sizes available in 220 or 120 volt, single phase!**

- Now it's easy to replace top loaders with new front loaders!
- New 5 year warranty!

**Wascomat Laundry Equipment**

1-800-645-2204 • [www.wascomat.com](http://www.wascomat.com)

*Wascomat — when laundry means business.*

| W-Series Models                               | W620cc       |           | W625cc       |           | W630cc       |           | W645cc       |           | W662cc       |           | W677cc       |           |
|---|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|
| Capacity (lb/kg)                              | 20           | 9         | 25           | 11        | 30           | 14        | 45           | 20        | 62           | 28        | 77           | 35        |
| Width (in/mm)                                 | 26           | 660       | 28 3/8       | 720       | 28 3/8       | 720       | 29 1/2       | 750       | 32 11/16     | 830       | 35 13/16     | 910       |
| Depth (overall) (in/mm)                       | 30 1/8       | 765       | 29 1/8       | 740       | 32 1/2       | 825       | 36           | 915       | 39           | 990       | 42 5/16      | 1075      |
| Height (in/mm)                                | 43 7/8       | 1115      | 47 1/4       | 1200      | 47 1/4       | 1200      | 52 3/16      | 1325      | 55 1/2       | 1410      | 56 7/8       | 1445      |
| Crated width - (in/mm)                        | 27 3/16      | 690       | 29 1/2       | 750       | 29 1/2       | 750       | 30 11/16     | 780       | 33 7/8       | 860       | 37           | 940       |
| Crated depth - (in/mm)                        | 32 11/16     | 830       | 35 1/16      | 890       | 37 3/8       | 950       | 39 3/16      | 995       | 43 11/16     | 1110      | 47 1/16      | 1195      |
| Crated height - (in/mm)                       | 48           | 1219      | 53 1/8       | 1350      | 53 1/8       | 1350      | 56 7/16      | 1434      | 61 1/4       | 1556      | 62 7/16      | 1586      |
| Height to bottom of door (in/mm)              | 14           | 355       | 14 3/8       | 365       | 14 3/8       | 365       | 17 1/8       | 435       | 18 1/2       | 470       | 19 11/16     | 500       |
| Door opening diameter (in/mm)                 | 12 3/16      | 310       | 14 3/8       | 365       | 15 9/16      | 395       | 15 9/16      | 395       | 17 1/8       | 435       | 17 1/8       | 435       |
| Cylinder volume (ft <sup>3</sup> /l)          | 3.0          | 85        | 3.7          | 105       | 4.6          | 130       | 6.4          | 180       | 8.8          | 250       | 11.7         | 330       |
| Cylinder diameter (in/mm)                     | 20 1/2       | 520       | 23 7/16      | 595       | 23 7/16      | 595       | 25 9/16      | 650       | 28 9/16      | 725       | 31 5/16      | 795       |
| Cylinder depth (in/mm)                        | 16 5/16      | 414       | 17 11/16     | 450       | 18 7/16      | 468       | 21 5/16      | 542       | 23 7/8       | 606       | 26 3/16      | 665       |
| Drain outlet diameter (in/mm)                 | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        |
| Height to centerline of drain (in/mm)         | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       |
| Height to electrical connection (in/mm)       | 32 1/2       | 825       | 35 13/16     | 910       | 35 13/16     | 910       | 40 3/4       | 1035      | 44 1/8       | 1120      | 45 1/2       | 1155      |
| Height to water connections (in/mm) (approx)  | 40 9/16      | 1030      | 43 7/8       | 1115      | 43 7/8       | 1115      | 49           | 1245      | 52 3/8       | 1330      | 53 3/4       | 1365      |
| Dynamic load (lb/kN)                          | 375+/-696    | 1.7+/-3.1 | 468+/-813    | 2.1+/-3.6 | 518+/-912    | 2.3+/-4.1 | 611+/-1057   | 2.9+/-4.7 | 842+/-1189   | 3.7+/-5.3 | 1019+/-1310  | 4.5+/-5.8 |
| Dynamic frequency (Hz)                        | 9.3          |           | 8.7          |           | 8.7          |           | 8.3          |           | 7.9          |           | 7.5          |           |
| Noise level (dBA)                             | 65           |           | 71           |           | 71           |           | 76           |           | 79           |           | 77           |           |
| Net wt (lb/kg)                                | 299          | 136       | 374          | 170       | 385          | 175       | 502          | 228       | 631          | 287       | 656          | 298       |
| Crated weight (lb/kg)                         | 330          | 150       | 403          | 183       | 431          | 196       | 528          | 240       | 664          | 302       | 700          | 318       |
| <b>Operating Speeds</b>                       |              |           |              |           |              |           |              |           |              |           |              |           |
| Wash (rpm)                                    | 52           |           | 46           |           | 46           |           | 44           |           | 42           |           | 40           |           |
| Extract (rpm/G-Force)                         | 587 / 100    |           | 548 / 100    |           | 548 / 100    |           | 525 / 100    |           | 497 / 100    |           | 474 / 100    |           |
| <b>Electrical Requirements (standard)</b>     |              |           |              |           |              |           |              |           |              |           |              |           |
| Voltage/frequency/phase                       | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           |
| Full-load current (Amps) / Ckt breaker (Amps) | 3.5 / 15     |           | 3.8 / 15     |           | 3.8 / 15     |           | 5 / 15       |           | 6.9 / 15     |           | 9 / 15       |           |
| Voltage/frequency/phase                       | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | -            |           |
| Full-load current (Amps) / Ckt breaker (Amps) | 7 / 15       |           | 7.6 / 15     |           | 7.6 / 15     |           | 9.5 / 15     |           | 13.2 / 20    |           | -            |           |
| <b>Water Information</b>                      |              |           |              |           |              |           |              |           |              |           |              |           |
| Inlet fittings (* = 3 inlets)                 | 3/4          | DN20      | 3/4          | DN20      | 3/4          | DN20      | 3/4*         | DN20*     | 3/4*         | DN20*     | 3/4*         | DN20*     |
| Flow (gpm/lpm @ 45 psi) (each inlet)          | 5            | 20        | 5            | 20        | 5            | 20        | 5            | 20        | 16           | 60        | 16           | 60        |
| Recommended water pressure (psi/kPa)          | 30-90        | 200-600   | 30-90        | 200-600   | 30-90        | 200-600   | 30-90        | 200-600   | 30-90        | 200-600   | 30-90        | 200-600   |

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Wascomat for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Wascomat assumes no responsibility for errors or omissions in this information.

## SUPERIOR WASH CYCLE CONTROL

With our Wash Program Manager software you can easily create custom wash programs on your PC.



### Compass Control

With multilingual Compass Control you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption—or create your own programs to meet the specific needs of your market. Easily program a higher price for hot washes, extra rinse and heavy soil. Program in discount prices for slow periods of the day or week.

Call today for information on the full line of Wascomat washers, dryers, flatwork ironers and low-cost financing and leasing.

**Wascomat** Laundry Equipment

1-800-645-2204 • www.wascomat.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@wascomat.com

Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@wascomat.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@wascomat.com

En Mexico: Llame gratis a este numero 001-800-010-1010

# 096201 5.19.10

Your local independent authorized dealer

